

215U-2 wireless I/O and gateway

802.11 b/g scalable industrial wireless I/O module
for reliable and secure connectivity



Wireless Solutions and Support Services



Description

The Eaton ELPRO 215U-2 wireless networking I/O and gateway is an integrated I/O node that extends communications in sprawling industrial applications to sensors and actuators in local, remote, or difficult to reach locations using standards based 802.11 b/g.

The 215U-2 provides robust/secure two-way wireless communications in extremely challenging indoor and outdoor industrial environments.

The internal radio transceiver is designed to operate reliably with the challenges of obstructed paths, typical of remote monitoring and control applications. Supporting base and ProMesh meshing functionality, the 215U-2 provides for reliable redundant networks in industrial applications. The 215U-2 configuration is quick and easy using built-in Web-based tool either directly at the unit or over the air, which also provides comprehensive diagnostic features.

Enabling Internet of Things (IoT) applications, the 215U-2 provides a powerful and versatile low-cost I/O connectivity solution for today's equipment and machines with a simple and easy-to-implement product to allow customers an easy way to get their devices on the Internet. The 215U-2 can also provide Ethernet and serial gateway support for industrial protocols including Modbus[®] TCP/RTU.

Features

- WPA2 secure 2.412–2.472 GHz frequency (802.11 b/g) 200 mW RF power
- I/O, Ethernet, or RS-232/RS-485 serial data and Modbus RTU/TCP gateway
- ProMesh intelligent communications network protocol
- Provides Wi-Fi hot-spot access to I/O data and dashboard
- Web-based dashboard allows monitoring and control of critical I/O
- Quick back-to-back I/O mode for cable replacement applications
- Over-the-air network configuration
- Expandable digital I/O for local alarms and inputs/outputs

Applications

- Machinery OEM I/O connectivity in factories—discrete sensors and digital I/O (e-Stops)
- Water and wastewater plant applications—flow and level sensors
- Oil and gas remote well sensor monitoring
- Electrical control panel hot-spot for remote monitoring of meters and control through PLC extension



Powering Business Worldwide



Wireless Solutions and Support Services

WWW.SpotcomLtd.co.uk

Specifications

Specification	Description
Transmitter and receiver	
Frequency ①	2.401–2.483 GHz 802.11 b/g
Transmit power ①	200 mW (+23 dBm)
Modulation	Direct sequence spread spectrum (DSSS) Orthogonal frequency-division multiplexing (OFDM)
Receiver sensitivity	–94 dBm (11 Mbps) 802.11 b –75 dBm (54 Mbps) 802.11 g
Channels ①	13 channels, 20 MHz
Data rate	1–54 Mbps (selects fastest connection rate available)
Typical range (LoS)	1300 ft (400 m)
Antenna connector	SMA female
Protocols and configuration	
System name	ESSID; 1- to 31-character text string
Protocols supported	TCP/IP, UDP, ARP, DHCP, ICMP, HTTP, FTP, VLAN 802.1Q, Modbus RTU, Modbus TCP
Configurable parameters	Unit details, I/O mappings and parameters, radio settings (refer to the user manual for details) Modbus TCP/RTU gateway Embedded Modbus master/slave for I/O transfer Ethernet mode, bridge (default), or router Prioritization of traffic flows, bandwidth efficiency features, bandwidth utilization, bridging, VLAN
User configuration	Via HTTPS Web server Network access: USB or Ethernet Remote access: over the air
Security	Data encryption, 802.11i with CCMP 128-bit AES Support for 802.1x radius server Secure HTTP protocol
Address filtering	Easy mode automatic filtering or advanced IP address, whitelist/blacklist MAC address, whitelist/blacklist ARP filtering, whitelist/blacklist
LED indications and diagnostics	
LED indication	Power/OK, Radio TX/RX/Link, RS-232, RS-485, digital I/O, analog I/O status
Reported diagnostics	
Radio diagnostics	RSSI measurements (dBm), connectivity information/statistics through Web page, dashboard, or local Modbus registers for SCADA
Connections	
LAN	1 x 10/100BASE-T auto-MDIX RJ-45
Serial	1 x RS-232, 1 x RS-485, 1200–230400 bps
Operation	
Modes	Base, mesh node, or manual setup for advanced configuration
Repeater and base	Maximum of 6 total remote/repeater/base/hot spot connections
Remote	Mesh node or fixed

Specification	Description
Input and output	
Discrete input ②	8 digital I/O (1–4 configurable as PI or PO) On-state voltage: <2.1 Vdc Wetting current: 5 mA Max. I/P pulse rate—DI 1/2: 50 kHz, DI 3/4: 1 kHz Max. I/P pulse width—DI 1/2: 10 µs, PI 3/4: 0.2 ms
Discrete output ②	8 digital I/O (1–4 configurable as PI or PO) Working voltage maximum: 30 Vdc Working current maximum: 200 mA Maximum O/P pulse rate—PO max. rate: 1 kHz
Analog input	4 AI (2 differential, 2 single ended) Current range: 0–24 mA Voltage input range: AI 1/2: 0–25 V, AI 3/4: 0–5 V Accuracy: 0.1% Resolution: 14 bits
Analog output	2 AO (sourcing) Current range: 0–24 mA Current resolution: 13 bits Accuracy (current): 0.1%
Analog loop supply	24 Vdc at 100 mA maximum (current limited)
Compliance	
EMC	FCC Part 15; EN 301 489-17; AS/NZS CISPR22
RF (radio)	FCC Part 15.247; IC RSS 210; EN 300 328; AS/NZS4268
Safety	EN/IEC 60950
Hazardous area	UL® Class 1, Division 2; Pending IEC EX Zone 2; ATEX Zone 2
Power supply	
Nominal supply	10.8–30 Vdc, undervoltage/overvoltage protection Sealed lead acid backup battery can be charged by main power supply input.
Average current draw	200 mA at 12 Vdc (idle), 100 mA at 24 Vdc (idle)
Transmit current draw	200 mA at 12 Vdc, 100 mA at 24 Vdc
General	
Size	5.91 x 7.09 x 1.38 in (150 x 180 x 35 mm)
Housing	IP20 rated high density thermoplastic
Terminal blocks	Removable, maximum conductor 12 AWG
Mounting	DIN rail
Temperature rating	–40 to +158 °F (–40 to +70 °C)
Humidity rating	0–90% RH noncondensing
Weight	1.1 lb (0.5 kg)

① Frequency range, number of channels, RF power specification may value depending on the country of application.

② Discrete input and output function shared for total of 8 discrete inputs and outputs.

Notes: Available RF power and frequency may vary depending on country of application. Please check user manual for your application.

Specifications subject to change.



Wireless Solutions and Support Services

WWW.SpotcomLtd.co.uk

Accessories

Product code	Description	Data sheet
Antennas		
ANTMD2400-EL	Dipole antenna, 15 ft (4.6 m) cellfoil/SMA, 0dBi gain, mounting bracket	TD032053EN
ANTSG2400-EL	Collinear antenna, N-type, 5 dBi gain, mounting bracket	TD032054EN
ANTZ2400-EL	Collinear antenna, N-type, 10 dBi gain, mounting bracket	TD032039EN
Cables		
CC3/10/20-SMA	Coaxial cable kit, 9.8 ft (3 m) / 32 ft (10 m) / 65 ft (20 m), N-type to SMA	TD032019EN
CCTAIL-SMA-F/M	Coaxial cable tail, 24 in (600 mm), SMA to N-type female or male	TD032023EN
CBLETH-C5A	Ethernet cable, 6 ft (1.8 m), straight through, RJ 45 to RJ 45	TD032024EN
Surge diverters		
CSD-SMA-2500	Coaxial surge diverter SMA male to SMA female	BU-SB13583
SURCSD-N-6000	Coaxial surge diverter, bulkhead N female to N female	TD032031EN
SURMA15/D/1/SI	Power supply surge diverter, 110 Vac / 15 A	TD032029EN
SURMA15/D/2/SI	Power supply surge diverter, 240 Vac / 10 A	TD032029EN
Mounting brackets		
BR-COL-KIT	Mounting bracket kit for collinear antenna	TD032071EN
Power supplies		
PSG60E	DIN rail power supply, 85–264 Vac, 24 Vdc / 2.5 A	TD032034EN
PS-WW-SP-24DC	24 Vdc 1.25 A ac wall adapter	TD032074EN

Ordering

Product code	Description	Frequency	RF power
EL-215U-2-BGN	Base/repeater/remote, 802.11 b/g I/O gateway, 9–30 Vdc	2.401–2.483 GHz	200 mW



Wireless Solutions and Support Services

WWW.SpotcomLtd.co.uk

Eaton
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com

Australia, New Zealand
9/12 Billabong Street
Stafford Queensland 4053
Australia
Telephone: +61 7 3352 8600

© 2017 Eaton
All Rights Reserved
Printed in USA
Publication No. TD032104EN / Z19415
April 2017



Wireless Solutions and Support Services

WWW.SpotcomLtd.co.uk

Eaton is a registered trademark.

All other trademarks are property
of their respective owners.